Near Net shape Technologies AlBeMet® NNSB and AlBeWeldtm

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

Brush Wellman Inc.
Beryllium Products Group
14710 W. Portage River S. Road
Elmore, Ohio 43416

(419) 862-4127 or (419) 862-4171 (419) 862-4174 (Fax) **Brush Wellman Inc.**

Larry Ryczek

Cell: (419) 351-3441

Phone: (419) 862-4341

Lawrence_H_Ryczek@brushwellman.com

Thomas B Parsonage Cell: (407) 341-0975

Phone: (407) 876-0952

Tom_Parsonage@brushwellman.com

Technology Days in the Government, September 17, 2003



Near Net Shape Technologies

- Near Net Shape HIP (Hot Issostatic Press)
 - Recent History
 - In Development under MAI Contract F33615-99-2-5215
 - Currently producing selected Prototypes
 - Broad Commercial availability
 - September 2004
- AIBeWeldTM
 - Spin-off from MAI Contract F33615-99-2-5216
 - In Development
 - Currently producing selected Prototypes and Orders
 - As reported properties
 - Parameters Optimized (.125" and Below)
 - Parameters in Investigation (.500" and Below)
 - Broad Commercial availability
 - March 2004



A More Disciplined Approach to NNSB using HIP AlBeMet®

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173


METALS AFFORDABILITY INITIATIVE (MAI)"Core" Program Cooperative Agreement F33615-99-2-5215



LiftFan Targeted for AlBeMet

14710 W. Portage River S. Road • Elmore, OH 43

- Joint Strike Fighter will be built in 3 versions.
- Version for Marines and British will be STOVL.





Lockheed X-35B STOVL Demonstrator Vertical Landing at Edwards AFB

The JSF aircraft will use a shaft driven LiftFan that converts 25,000 HP into 18,000 lb vertical thrust.

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

HIP Shaped Blank



Experimental Plan

- Produce Constituent Data for Finite Element Modeling (FEM)
- HIP .67 Scale Intermediate Bearing Support to Establish Feasibility and Provide Iterative Step to Improve FEM Capability
- HIP Full Scale Intermediate Bearing Support to Validate FEM

HIP'ing complex cans designed by FEM will provide cost effective blanks for machining components



14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

HIP Shaped Blank

Development & Optimization Plan

- HIP Several Iterations of the Full Scale Intermediate Bearing Support to Optimize Blank Design for Cost Effectiveness
- Establish Material Property Relationship Between Shaped Blank Component and Ride Along Can



Development, optimization and material properties to be developed with outside funding.




Actual NNSB Part JSF Lift Fan 2/3 Scale Part

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

Top View

Bottom View








NNNSB (Near Net Shape Blanks) Recent History


14710 W. Portage River S. Road • Flmore OH 43416 • (419) 862-4127 or (419) 862-4173

Honeycomb monolithic mirrors blanks





Monolithic Close Back Cell







Detailed Experimental Plan Intermediate Bearing Support

HIP'ed Blank & Machine Development

Design Review

- Rolls Royce provides drawing
- Brush Wellman reviews design with HIP can designer, Synertech
- Can specification written
 - Consolidation factor
 - HIP tolerances
 - Be-Al blank dimensions
- Synertech/Brush Wellman design and produce HIP can

Development

- Develop FEM HIP model
- Fabricate 2/3 Scale HIP can
- HIP consolidate prototype part
- Evaluate dimensions compared to Model
- Adjust design to full scale can as needed
- Establish mechanical property relationship between ride along can, part & HIP'ed data base
- Optimize and validate process

Product Evaluation

- Blend chemistry
- Dimensional map
- Density test of part & ride along can
- Tensile test ride along can
- Remove the can mechanical or chemical machining
- Dye penetrant after Rough Machining

EKV Drop-in Replacement using O-30 Beryllium

Cost Estimate



Price Comparison EKV Sunshade NNSB

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

- Price for material by current billet machined approach
 - Material Only
 - (15) PC Baseline

100%

Price for material by NNSB (Initial ROM)

• (15) pieces

60-65% of Baseline

NRE/Tooling

\$27,500.

- Based on ROM fabrication costs a price equal to 70-75% of the baseline for this "Drop-in Replacement" is possible.
- Requires only a specification change from S-200F to O-30H.



AlBeMet®/Beryllium NNSB Summary

- Demonstrated the capability to model Near Net Shape Blanks
 - Use of external and internal mandrels
 - Both re-usable and expendable
- Open Back Net Shape, Lightweight Optical Mirror Blanks:
 - Scalable to the 1 meter size range
 - AlBeMet® or Beryllium Spherical Powder
 - Can be demonstrated in the near future



AlBeMet® NNS Technologies using Wrought Alloys

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

METALS AFFORDABILITY INITIATIVE (MAI) "Dust" Program Cooperative Agreement F33615-99-2-5216

E-Beam Welding Spin-off



AlBeWeldTM

Aluminum Beryllium E-Beam Welding



Why AlBeWeldTM?

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

Goals of the Technology

- Achieve the material cost benefit of a "brazement" with the material properties of monolithic
 AlBeMet
- Combine Smaller pieces together to make parts larger than possible with current capabilities
- Incorporate machine features on smaller pieces with lower costs than on complex, larger blanks

AlBeMet® Solid Block 107.5 Lbs. 1 solid block 9.32" x 9.35" x 16.2

AlBeWeld Blank 45.8 Lbs.

Piece 1 - 1.80" x 9.87" x 9.32"

Piece 2 - 1.90" x 9.32" x 9.35"

Piece 3 - 1.20" x 9.32" x 12.70"


Piece 4 - 1.25" x 9.32" x 12.70"

Part 2
Part 4
Part 4



Finished Part 10 Lbs.


The Progression of a Weld Joint (.191" thick)



Base metal is typical microstructure of AlBeMet 162



At the edge of the weld zone, microstructure is coarser than the center and finer than the base metal.



Center of weld zone is the finest microstructure in this specimen.



AlBeWeld TM Capabilities

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

Internal

- Hamilton Standard 52" EB Welder
 - EB Welder controls are 2 axis
 - 7.5 KW Capability
- Working space 36"(Y) x 23"(Z) x 52" (X)
- AM162 can be welded in thinner sections

Partner

- EB Welder can accommodate 54"(Y) x 40"(Z) x 108"(X)
 - 25 KW capability
 - Larger Sizes Possible
- EB Welder controls are 5 axis plus rotation
- We have welded material at .125" thick. Material up to 0.5" thick is expected to produce high quality welds.




Weld Joint Interface 1/2" Thickness





Double Weld Intersection



AlBeWeld Prototype Development



AlBeWeld Prototypes

- Gimbal Prototypes
 - Two Concept Prototypes Complete.
 - We should expect to get an order for two Engineering Development Units.
- Optical Barrel Repair
- ROM Estimate for the EKV Sunshade




Gimbal Weld Blank Prototypes







Gimbal Weld Joint - Post Machining





AM162HIP Weld Results

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

Weld Tensile Results - HIP Block (Gimbal Prototype)

	UTS	YS	% Elongation			
PM	45.9	34.8	4.7			
PM	44.9	37.2	4.3			
Cond						
A	46.1	33.5	3.9			
Α	43.3	33.9	2.5			
Cond						
В	40.5	32.6	1.6			
В	40.7	33.2	1.6			





Electron Beam Welded AM162HIP 400X - Thickness .400" sample



Specified Mechanical Properties of Aluminum-Beryllium AM162

Material Type	Heat Treatment	Yield Strength MPa (KSI)	Ultimate Strength MPa (KSI)	Elongation %
HIP	593°C/24 hours	191 (28)	262 (38)	2
Typical	593°C/24 hours	(30-32)	(42-43)	4-5
Weld Strengths (as tested)	None	(32-33)	(40-46)	1.6-4.0
Extruded (L/T)	593°C/24 hours	276 (40)/276 (40)	279 (55)/330 (48)	7/2
Typical	593°C/24 hours	(45-48)/(45-48)	(60-65)/(55-58)	8-10/2-4
Weld Strengths (as tested)	None	Not tested	Not tested	Not tested
Sheet	593°C/24 hours	276 (40)	344 (50)	5
Typical	593°C/24 hours	(44-46)	(56-58)	5-7
Weld Strengths (as tested)	None	(42-44)	(50-52)	.8-1.8

AlBeWeld Repair!!!!



Optical Barrel Repair Problem


- AlBeWeld Repair
 - Problem
 - Optical Barrel ID was Machined Oversized
 - Solution
 - Remove oversized section and EB Weld a new repair ring to the top of the Optical Barrel.



Optical Barrel Repair Process

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

Welding Process



BRUSHWELLMAN
BERYLLIUM PRODUCTS GROUP
www.brushwellman.com

Optical Barrel Repair

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173


12" Weld Test Coupon





Optical Barrel Repair





B-B

Optical Barrel Cross-Section View



Optical Barrel Repair

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

Optical Barrel and Fixture




Weld Joint



EKV Sunshade Fabrication Approach

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

2. Form sheet into tube, then seam weld



1. Machined Flanges from Tube Stock

3. Assemble into fixture, E-Beam Weld, Finish Machine, assemble, coat



Price Comparison EKV Sunshade E-Beam Welded

14710 W. Portage River S. Road • Elmore, OH 43416 • (419) 862-4127 or (419) 862-4173

- Price for completed Sunshade by current billet machined approach
 - (15) PC Baseline

100%

- **ROM Price for fabricated component (Initial ROM)**
 - (15) PC Percent of Baseline

42.5-47.5%

NRE/Tooling

\$17,500.

Requires a specification change from S-200F to AM162 (70% Be/30% 1100 Aluminum by vol.) and a thinner wall (to match weight).



AlBeWeldTM Summary

- E-Beam welding has been successfully demonstrated for:
 - Scale up from .100" Thickness to .500" Thickness
 - High strength (Close to Parent Metal)
 - 50-75% of the Parent Metal Ductility
 - Joining without filler metals
 - CTE compatible
 - Repair of expensive AIBeMet® structures

Next Steps

- Phase 1 Samples at .350" and .500"
 - Welding complete
 - Visual results excellent
 - Properties and Metallurgical Evaluation in Progress
- Phase 2
 - DOE to optimize parameters with Properties
 - In development
 - Expected Start later this month
- Prototypes
 - Several applications in development/design
 - Already delivered acceptable parts up to .500" Thick

